

LD-DSM150

Intelligent deodorising and sterilising machine

Adopting high-energy ion deodorisation technology, plasma catalytic purification technology and plant liquid deodorisation technology, the odour removal rate is more than 90% and the bactericidal rate is more than 95%, adopting six core technologies, five levels of purification, adjustable deodorisation capacity, intelligent fault protection, low power consumption, large area of action, 360°dead-angle-free purification.

Built-in EnOcean wireless communication module, can be linked with other EnOcean devices, can also be paired with wireless switch, remote control on or off.



Basic Parameter

Maximum airflow	150m ³ /h
Effective deodorisation area	≥15 m ²
Noise	≤50db
Ammonia removal efficiency	≥95%
Other Odour Removal Rate	≥90%
Sterilisation Rate	≥95%
Purification Module	Intermediate filters, high-energy ion purification tubes, plasma catalytic network, all-natural plant deodorant balm
Rated Voltage	220VAC/50Hz
Power	20W

Mechanical parameters

Sizes	495x280x175mm
Net Weight	6.5kg
Mounting	Wall mounting



7F, Building A2, Block 5,
No.1 Putian Road,
Qinhuai
District, Nanjing, China

Tel:
+86 025 5260 9811
Fax:
+86 025 5260 9811

